



DETAIL 1: TOILET UNIT PLAN SCALE: 1/16

DETAIL 2: TOILET UNIT SECTION SCALE: 1/16

**GENERAL NOTES:**

1. UNITS ARE SEALED WITH BUTYL TAPE AT THE JOINTS
2. EXCAVATION MUST BE READY, SAFE AND ACCESSIBLE FOR UNLOADING FROM THE REAR OF THE TRUCK.
3. MIN OVERHEAD CLEARANCE OF 18FT (5.5 METRES) IS REQUIRED
4. ALL UNITS MUST BE HANDLED WITH PROPER LIFTING EQUIPMENT (I.E. SPREADER BAR)
5. SCHEMATIC ONLY (FURTHER DETAIL UPON REQUEST)
6. MAXIMUM BURIAL DEPTH = 1 METRE IN FIRM SOIL AWAY FROM ANY VEHICULAR TRAFFIC

**\*CONCRETE BUILDING OPTIONS AVAILABLE\***



**MANUFACTURED:**  
OTTAWA, ON  
1-800-655-3430

**CONCRETE:** 45MPa at 28 days/6,500PSI  
**AIR ENTRAINMENT:** 5-8%  
**REINFORCEMENT:** STEEL TO CSA CAN A23.1 /A23.3 G30.14-M1983

**WEIGHT:** TOP: 16,000lbs / 7,250kg  
BOTTOM: 16,000lbs / 7,250kg  
**CSA APPROVED**  
MEETS CAN/CSA-B66 "AGIN"

**DRAWN BY:**  
N.CHAN

**DATE:**  
MAR/2021

**PRIVY 14000** (WOOD STRUCTURE)

14,000 LITRES