



- GENERAL NOTES:**
1. UNITS ARE SEALED WITH BUTYL TAPE AT THE JOINTS
 2. EXCAVATION MUST BE READY, SAFE AND ACCESSIBLE FOR UNLOADING FROM THE REAR OF THE TRUCK.
 3. MIN OVERHEAD CLEARANCE OF 18FT (5.5 METRES) IS REQUIRED
 4. ALL UNITS MUST BE HANDLED WITH PROPER LIFTING EQUIPMENT (I.E. SPREADER BAR)
 5. SCHEMATIC ONLY (FURTHER DETAIL UPON REQUEST)
 6. MAXIMUM BURIAL DEPTH = 1 METRE IN FIRM SOIL AWAY FROM ANY VEHICULAR TRAFFIC
 7. TUF-TITE SAFETY LID INSTALLED IN OPENING AS PER CSA-B66-21

CONCRETE BUILDING OPTIONS AVAILABLE



MANUFACTURED:
OTTAWA, ON
1-800-655-3430

CONCRETE: 45MPa at 28 days/6,500PSI
AIR ENTRAINMENT: 5-8%
REINFORCEMENT: STEEL TO CSA CAN
A23.1 /A23.3 G30.14-M1983

WEIGHT: TOP: 19,365lbs / 8,784kg
BOTTOM: 19,365lbs / 8,784kg
CSA APPROVED
MEETS CAN/CSA-B66
"AGINP"

DRAWN BY:
JAY PATEL

DATE:
APRIL/2022

PRIVY 18000 (WOOD STRUCTURE)

18,000 LITRES