



2-NESTED FIRE WATER TANKS

30000 LITRES
6600 IMPERIAL GALLON

TOTAL CAPACITY: 33,918 LITRES TO UNDERSIDE OF CHAMBER LID
PER TANK

GENERAL NOTES:

1. CAS 603- CAST CLOSE AS POSSIBLE TO THE BOTTOM OF TANK
2. UNITS ARE SEALED WITH BUTYL TAPE AT THE JOINTS
3. DELIVERY IS MADE BY CRANE-EQUIPPED TRUCKS
4. EXCAVATION MUST BE READY, SAFE AND ACCESSIBLE FOR UNLOADING FROM THE REAR OF THE TRUCK.
5. MIN OVERHEAD CLEARANCE OF 18FT IS REQUIRED
6. ALL UNITS MUST BE HANDLED WITH PROPER LIFTING EQUIPMENT (I.E. SPREADER BAR)
6. MAXIMUM BURIAL DEPTH = 1 METRE IN FIRM SOIL AWAY FROM ANY VEHICULAR TRAFFIC



MANUFACTURED:
BROOKLIN, ON
1-800-655-3430

CONCRETE: 35MPa/5000PSI
AIR ENTRAINMENT: 6-8%
MEETS CAN/CSA-B66-00
REINFORCEMENT: STEEL TO CSA CAN
A23.1 /A23.3 G30.18 Fy=400MPa

WEIGHT: 40,905lbs / 18,555kg
CPA CERTIFIED

DRAWN BY:
S. RIMLAND

DATE:
JAN/2018