



TOP VIEW
SCALE: 1/40



SECTION A
SCALE: 1/40



SECTION B
SCALE: 1/40

- GENERAL NOTES:**
1. UNITS ARE SEALED WITH BUTYL TAPE AT THE JOINTS
 2. DELIVERY IS MADE BY CRANE-EQUIPPED TRUCKS
 3. EXCAVATION MUST BE READY, SAFE AND ACCESSIBLE FOR UNLOADING FROM THE REAR OF THE TRUCK.
 4. MIN OVERHEAD CLEARANCE OF 18FT (5.5 METRES) IS REQUIRED
 5. ALL UNITS MUST BE HANDLED WITH PROPER LIFTING EQUIPMENT
 6. MAXIMUM BURIAL DEPTH = 1 METRE IN FIRM SOIL AWAY FROM ANY VEHICULAR TRAFFIC
 7. MINIMUM BIONEST SECTION VOLUME TO BE: **5390L**
CURRENT CAPACITY: **5447L**

BST-2600-BCP SEPTIC TANK

POS.	PART #	DESCRIPTION	QUANTITY
1	413561	BST-2600-BCP	1
2	408167	POLYLOK PLASTIC RISER 24"dia X 6"h	6
3	450027	POLYLOK LID 24"dia - DOMED	2
4	450046	POLYLOK LID 24"dia - VENTED LID	1
7	*SUPPLIED BY BIONEST*	FLEXIBLE AIR DIFFUSER (1m)	1
8	*SUPPLIED BY BIONEST*	AIR LINE PIPE	1
9	*SUPPLIED BY BIONEST*	BIONEST MEDIA BAG	10
10	112581	TUF-TITE EF-6" T-BAFFLE	2
11	408144	TUF-TITE EFFLUENT FILTER 6" C/W T-BAFF	1
12	112707	4 x 16" SOLID SEWER PIPE	3
13	408041	PVC TEE 4"	1
14	*SUPPLIED BY BIONEST*	Ø1-1/2" PVC ELBOW 90° BELL-END TO FACE UPWARD	1
15	*SUPPLIED BY BIONEST*	ABS PLASTIC STRIPS 5" x 24"	3
16	*SUPPLIED BY BIONEST*	AIR DIFFUSER CAGE 3.5" x 23"	3
17	106470	4" CAST IN COUPLER	1
18	112167	4" CAST.A.SEAL #452.0450	2
19	112167	4" CAST.A.SEAL #452.0450 (CLOSED FACE)	2
20	450103	POLYLOK 20" SAFETY LID	3



MANUFACTURED:
BROOKLIN, ON
1-800-655-3430

CONCRETE: 35MPa at 28 days/5000PSI
AIR ENTRAINMENT: 5-8%
REINFORCEMENT: STEEL TO CSA CAN
A23.1 /A23.3 G30.18 Fy=400MPa

UNIT WEIGHT: 17,895lbs / 8,120kg
BNQ CERTIFIED
MEETS CAN/CSA-B66

DRAWN BY:
JAY PATEL
DATE:
MAY/2022

BST-2600-BCP
9000L / 2000 IMPERIAL GAL. BIONEST TANK
WORKING CAPACITY: 9,207L TO INVERT OF OUTLET
TOTAL CAPACITY: 10,962L TO UNDERSIDE OF CHAMBER LID